

Rapid Accessories



A **Charging adaptor** is available. Screw bottle up hand tight. This can then be charged at a diving centre using 'A' frames clamp. Do not exceed 3000 psi on 12ft/lbs rifles or 3200 psi on FAC rifles.

DIN Fitting This 5/8 BSP male to 1/4 BSP female adaptor is used to convert some charging units to allow Rapid bottles to be filled. The DIN fitting does not use the buddy bottle oring to make an airtight seal, it uses a delrin seal (supplied). So MFR bottles can be charged with no problem.

Decant set for filling buddy bottles. Built as one unit it consists of bleed block, gauge and 'A' clamp. This will fit all air reservoir bottles similar to those used by divers.

- 1 Clamp the decant set to the main reservoir bottle.
- 2 Screw in the buddy bottle - hand tight.
The top of the buddy bottle seals on the delrin seal.
- 3 Check the bleed screw is finger tight.
- 4 Open the main valve allowing the air to fill the buddy bottle. (Only fill 280cc bottles slowly to prevent burning out Schrader valve).
- 5 Open bleed valve 2 - 3 turns, until excess air has been expelled.
- 6 Remove the filled buddy bottle and fit on Rapid.



Rapid buddy bottles are available in 400cc and 280cc. The 280cc bottle available for 12ft/lbs .22cal Rapid only.

Buddy bottle cap is made in steel with a delrin seat. This heavy duty cap will protect the buddy bottle when not on the gun and gives extra reassurance that the bottle is totally sealed. Fitted as standard on all 400cc bottles.

Rapid MFR buddy bottle This 280cc bottle is has a brand new designed fitting in the top to allow it to give better use of the air. Another noticeable difference is the lack of the external oring seal around the neck. This bottle is only compatible with the MFR and will not work on other models of Rapid.

12ltr (300bar) Reservoir Bottle

Simply screw in the buddy bottle hand tight. Open the knob to fill the bottle to the recommended filling pressure. Close knob and pull upwards to bleed off surplus air. Unscrew the buddy bottle.

For refilling at a diving centre it may be necessary to use the charging adaptor that is supplied with the rifle.

NOTE: The buddy bottles will not fill if the white delrin seal is missing. Air will come out of the area where the bottle is screwed in.



Bottle O-rings

Screwing the buddy bottles on and off the Rapids means that the bottle o-ring can wear or get damaged over time preventing it from sealing fully. So we supply replacement bottle o-rings individually.

O-ring Grease (Molykote 33)


We recommend that a small amount of this grease is wiped on the bottle o-ring every 5 to 6 fills to prevent this o-ring getting damaged and leaking. e 100g



The **Large Bolt Handle** is available and can be fitted to your original Rapid Mkl.

Rapid Service Kits

If your Rapid is starting to feel tired and used you have two options; the first is to purchase a service kit from us. This contains a brand new black valve, o-rings, tools and instructions on how to service your Rapid or trouble shoot a problem you may be having. Although, if you are not technically minded or you would prefer a this work to be carried out professionally we can service and test any of our rifles.



Magazines



7 Shot
.22 calibre only



12 Shot
.20, .22, .25 calibres



17 Shot
.177 calibre only

Don't forget; Theoben can service or repair Rapid (& SLR) magazines to give you many years of trouble free use.

Single Shot Holder

Allows the shooter to carefully select each pellet and load it individually. This is extremely popular with field target shooters. Supplied with the Rapid MFR but now available to all Rapid owners. Fits into the magazine slot - no modifications required.



The FAC rated Rapids

Extend your effective range with one of our high powered air rifles. Many situations call for more power than the UK limit of 12 ft/lbs, but due to safety concerns a Long Rifle can be too powerful. But with excellent accuracy, long distance shots can be taken with total confidence and energy of a .20 calibre using 14 grain pellet is in excess of 12 ft/lbs at 100 yards, it is extremely capable of carrying out any job in hand.

UK FIRE ARMS LAWS: To obtain a Fire Arms Certificate you will need to contact the Fire Arms Officer at your local police station. Applications for an FAC air rifle are now more favourably viewed than for other more powerful weapons.

Convert Your Rapid to FAC Specification

If you have a .20 or .22 calibre Rapid it can be converted at the factory to FAC. This conversion uses your existing 16" barrel. Some efficiency will be lost compared with the 19 inch barrel FAC versions, but you can still expect over 24 ft/lbs for .20 calibre and 26 ft/lbs for .22 cal. However the benefit is a shorter, lighter rifle for easier use. If you wish to convert your .177 calibre Rapid a 19" barrel must be purchased to get the power/shots, as this length of barrel is more efficient.

REMEMBER: Theoben can service or repair any rifle, bottle or magazine that we manufacture.